

DESTROYIT® 4107

Wide feed table and powered conveyor for fast, efficient feeding. Equipped with a convenient centralized oiler.

Security level P-2	12 mm strip-cut (1/2 inch)
Sheet capacity:	120-140*
Security level P-2	9 mm strip-cut (3/8 inch)
Sheet capacity:	105-125*
Security level P-2	6 mm strip-cut (1/4 inch)
Sheet capacity:	75-95*
Security level P-3	6 x 50 mm cross-cut (1/4 x 2 inches)
Sheet capacity:	65-82*

*Certified using 8 1/2" x 11" 20 lb. bond and recommended power supply.



max.
140
sheets
← 16" →

Powered conveyor belt feed system. Convenient centralized oiler for lubrication of the cutting shafts. Safety lock and key, main switch, and emergency stop button. Automatic power cut-off when cabinet is opened or shred bag is full. Automatic reverse and power cut-off when overfed. Thermal switch prevents overheating. Removable side tables provide large work space. Push button control panel with optical indicators to show operational status. Soft metal resistant, hardened steel cutting shafts take CDs / DVDs and hardbound documents. High powered 3 phase motor rated for continuous operation. Fully enclosed gear box housing. Mounted on heavy duty casters. Rear opening cabinet door and mobile shred bag suspension frame for easy replacement of shred bags.

Specifications

Shred volume, gallons	79
Feed opening, inches	16
Electrical requirements, volts	220, 3 phase
Maximum horsepower	10 (sc), 8 (cc)
Dimensions (D x W x H), inches	67 x 48 3/4 x 56 3/4 ¹
Shipping weight, pounds	952 (12 and 9 mm sc), 994 (6 mm sc), 983 (cc)

¹transportation width (minus side tables) is 27 inches

*High Capacity models have a 1 year limited warranty.

WWW.MBMCORP.COM
TEL: 800-223-2508

WWW.IDEAL-MBM.COM
TEL: 800-387-2528

DESTROYIT® 4107

Features



SIMPLIFIED CONTROLS

Operation is controlled by an ergonomic control panel. Optical indicators display operational status.



MOBILE SHRED BAG SUSPENSION FRAME

Caster-mounted bag suspension frame is easily removable through the rear cabinet door. Shredder stops automatically when door is opened.



CENTRALIZED OILER

Conveniently located centralized oiler provides quick and easy lubrication of the cutting shafts.



CONVEYOR BELT

Conveyor belt feed system allows fast, efficient shredding while eliminating jams. Bulky materials such as crumpled paper can be smoothly fed into the cutting unit.



*High Capacity models have a 1 year limited warranty.