

# TOSHIBA

## e-STUDIO™ 389cs/479cs

- > Full Color Multifunction Printers
- > 40 & 50 PPM
- > Letter/Legal Size
- > Medium Workgroup
- > Copy, Print, Scan, Fax



# PROFESSIONAL COLOR PRODUCTION FROM THE COMFORT OF YOUR OWN OFFICE.

Toshiba's new e-STUDIO389CS and e-STUDIO479CS offer printing at up to 40 and 50 pages per minute respectively\*, superior print quality, enhanced security and expertly engineered durability. All of which is powered by a quad-core processor that maximizes performance. With scanning at up to 60 ipm, your information can be quickly captured and made available to you and your network applications.

## Brilliant in-house color you can afford.

- > Accurately and affordably match all your brand colors and other color output.
- > Produce critical colors with our advanced technology that combines RGB and spot color replacement.
- > Design with perfect color matching from the get go combining PANTONE® calibration and embedded color sample pages.

## Impressive speed, functionality and reliability at your fingertips.

- > All the power you'll need is built in, thanks to a quad-core processor print controller.
- > Even your large color print jobs are completed quickly, with print speeds of up to 40 and 50 ppm, respectively.\*
- > Minimize wait times by printing a single color page in as little as 6 and 5 seconds, respectively.
- > Save even more time by conveniently printing from flash drives, network drives and online servers.

## Now your workflow involves less work.

- > Keep things flowing smoothly with digital workflows as well as paper documents.
- > Quickly capture and access information directly and from your network applications using scans speeds up to 60 ipm.

## Keep your sensitive data secure.

- > Control access to the MFP with full device authentication using convenient, yet secure card readers.
- > Port and connection filtering further tighten access.
- > 256-bit AES encryption and hard disk wiping keep sensitive print job data secure.
- > Digital signatures on firmware updates ensure that only legitimate updates are accepted by the device.

## Save costs and the environment.

- > Reduce power usage and costs with multiple power-saving modes. Sleep mode uses less than 3 watts between jobs. Hibernate mode uses less than half a watt during scheduled on/off periods.
- > Save even more resources and energy with standard double-sided printing and low-heat fusing toner.
- > Be confident you're reducing energy costs with this EPEAT® Silver rated and ENERGY STAR® certified device.



Toshiba e-STUDIO479CS with 7" touch screen interface. Shown with optional 550-sheet tray (Part # KD1070 and STAND478S).

\*Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT).

\*\*Average standard page yield value declared in accordance with ISO/IEC 19752.

## YOUR WISH IS ITS COMMAND, SIMPLE AS THAT.

### User friendly from the get-go.

- > Meet a familiar interface with its tablet-like design and smart-touch technology.
- > Access the features you need quickly and easily using its flat menu structure.
- > No special training required to use the Embedded Web Server.
- > Take advantage of slick, PC-free printing from a thumb drive or network share—whether it's MS Office documents (XLS, PPT, DOC), PDFs or image files.
- > Your workday is made even easier with a variety of apps that come standard.



User friendly 7" tablet-style touch screen display.



# e-STUDIO™ 389cs/479cs

## Main Specifications

<b>Copy System</b>	Indirect Electrostatic Photographic Method/OPC/Laser Printing/ Heat Roller Fusing
<b>Display</b>	7" Color TFT Touch Screen Tilting Display
<b>Copy Speed</b>	40 PPM/50 PPM (LT)
<b>First Copy Out</b>	As Fast as 6/5 Seconds Black, 6.5/5.5 Seconds Color
<b>Warm-Up Time</b>	Approx. 90 Seconds
<b>Copy Resolution</b>	Up to 600 x 600 dpi
<b>Multipurpose Tray</b>	3.0" x 5.0" to LG, Envelope
<b>Multiple Copying</b>	Up to 999 Copies
<b>Paper Capacity</b>	Standard 650 Sheets/Max. 2,300 Sheets
<b>Original Feed</b>	Standard 100-Sheet RADF
<b>Scan Speed</b>	RADF Scan: 20 IPM (600x600) Photo/Quiet, 40 IPM (600x300) Normal, 60 IPM (600x300) Express
<b>Max. Original Size</b>	LG
<b>Paper Feed Sizes</b>	Drawer 1: 550 Sheets - 4.13" x 5.83" to LG Multipurpose Tray: 100 Sheets - 3.0" x 5.0" to LG Opt. Drawers: 550 Sheets - 4.13" x 5.83" to LG Drawers: 16lb - 58 lb Bond
<b>Paper Weights</b>	Standard Automatic Duplex Unit: 16 - 32 lb Bond
<b>Duplex</b>	25% to 400%
<b>Reproduction Ratio</b>	Max. 120K/150K Month
<b>Max Duty Cycle</b>	Approx. 99 lb
<b>Weight</b>	19.9" (W) x 21" (D) x 25.5" (H)
<b>Approx. Dimensions</b>	20K, CMY: 13K @ 5%
<b>Toner Yield</b>	120 Volts, 50/60 Hz, 15 Amps
<b>Power Source</b>	Maximum 1.5kW (120V)
<b>Power Consumption</b>	1.2GHz (Quad-Core)
<b>CPU</b>	2GB/4GB
<b>Memory, Std./Max.</b>	320GB HDD (Optional on e-STUDIO389CS)
<b>Hard Disk Drive</b>	

## Print Specifications

<b>PDL</b>	PostScript 3, PCL 6, PCL 5, PPDS, PDF v1.7, XPS, HTML, Direct Image, MS Office
<b>Print Speed</b>	40/50 Pages Per Minute (LT)
<b>Print Resolution</b>	1200 x 1200 dpi, 600 x 600 dpi
<b>Standard Ports</b>	Rear USB 2.0 Specification High Speed Certified Port (Type A), Front USB 2.0 Specification High Speed Certified Port (Type A), Gigabit Ethernet (10/100/1000), USB 2.0 Specification High Speed Certified Port (Type B), One Internal Card Slot
<b>Optional Network Ports</b>	WiFi Option/Internal 1284-B Bidirectional Parallel, Internal RS-232C Serial
<b>Device Management</b>	Embedded Web Server
<b>Accessibility Features</b>	Tilt Front Panel, 508 Accessibility Support, Voice Guidance
<b>Security Features</b>	Role Based Access Controls, Ease of Use for User Access Control, Breach Mitigation, Moving Processes Off of Root (Emulators, Network, Security), Secure Element SmartCard, Protect Encryption Keys for Hard Disk, Protect Device Certificates, Provide True Random Number Generation to Meet Next-Gen FIPS and CC Requirements, Customer-Installable, Option, Unified Integrated Address Book, Common Admin Management for Internal & eSF App Contacts, Configuration via EWS, Supports Device Quotas App, Common Criteria Certification, PKI/SCAC Support, Setup Local Accounts on Operator Panel
<b>Environmental Features</b>	Sleep & Hibernate Modes, Eco Mode, Quiet Mode, Blue Angel/RAL-UZ-122 Certification, RoHS Compliant
<b>Certifications</b>	Energy Star Certified, EPEAT Silver, Mercury Free, Support for Recycled Paper
	WHQL (Windows 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell, Citrix, SAP

## Scan Specifications

<b>Scan Speed</b>	RADF Scan: 20 IPM (600x600) Photo/Quiet, 40 IPM (600x300) Normal, 60 IPM (600x300) Express
<b>Scan Destinations</b>	USB Thumbdrive, E-Mail, FTP, Network or USB Connected Computer, Windows Network Folder
<b>Scan Resolution</b>	600 dpi (Max)
<b>File Formats</b>	TIFF, JPG (JPEG), PDF (Regular, Secure, Archival (PDF/A), Searchable (HDD option req'd for e-STUDIO389CS)), XPS
<b>Image Compression</b>	PDF - 1 bit - JBIG2, CCIT G4, Flate, 8/24 bit - Flate, JPEG TIFF - 1 bit - CCITT G4, 8/24 bit - Packbits, LZW JPG - 8/24 bit - JPEG

## Facsimile Specifications

<b>Compatibility</b>	Super G3
<b>Transmission Speed</b>	Approx. 3 Seconds Per Page
<b>Fax Modem Speed</b>	Up to 33.6 Kbps
<b>Fax Shortcuts</b>	500 - Based on an Average Shortcut 25 Characters for Name, 10 Characters for Number and 4 Characters for Shortcut Id. Maximum Characters - 512 and Each Location Separated by a Semi Colon. 46 Locations Using a 10-Digit Phone Number, 64 Locations Using a 7-Digit Phone Number
<b>Group Fax</b>	400 Locations - Each Number in a Fax Shortcut is a Location

## Accessories (Options)

550-Sheet Tray	KD1070
2GB DDR3, G2, 512Mx32, 204 SODIMM	GC1450
256MB User Flash Memory	GC1430
SATA 500GB HDD (Std. on e-STUDIO479CS)	GE1250
Forms and Bar Code Card	GB2080LXX
IPDS Card	GB2100LXX
PRESCRIBE Card	GB2090LXX
Contact Authentication Device	GB2140LXX
Contactless Authentication Device	GB2150LXX
MarkNet 8360 Wireless	GN1180
RS-232C Serial Interface Card	GF1260
Parallel 1284-B Interface Card	GF1250
Security Element (Smart Card Feature)	GB2130LXX
MFP Stand (13.5" High)	STAND479CS
Casterbase (3.5" High)	CASTERBASE479CS
Power Filter	PWRFLTR-S1

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).



Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

### Corporate Office

### East Coast

### Midwest

### South

### West Coast

### Web Site

25530 Commercentre Drive, Lake Forest, CA 92630  
Tel: 949-462-6000  
959 Route 46 East, 5th Floor, Parsippany, NJ 07054  
Tel: 973-316-2700  
8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631  
Tel: 773-380-6000  
2037 Bakers Mill Rd., Dacula, GA 30019  
Tel: 678-546-9385  
25530 Commercentre Drive, Lake Forest, CA 92630  
Tel: 949-462-6000  
[www.business.toshiba.com](http://www.business.toshiba.com)